

ATGBICS ABCU-5741RZ Avago Broadcom Compatible Transceiver SFP 10/100/1000Base-T (RJ45, Copper, 100m)

Brand : ATGBICS

Product code: ABCU-5741RZ-C

Product name : ABCU-5741RZ Avago Broadcom Compatible Transceiver SFP 10/100/1000Base-T (RJ45, Copper, 100m)



ABCU-5741RZ Avago Broadcom Compatible Transceiver SFP 10/100/1000Base-T (RJ45, Copper, 100m)

ATGBICS ABCU-5741RZ Avago Broadcom Compatible Transceiver SFP 10/100/1000Base-T (RJ45, Copper, 100m):

ATGBICS ABCU-5741RZ-C SFP operates on standard Category 5 unshielded twisted-pair copper cabling of link lengths up to 100m. Our Avago compatible ABCU-5741RZ-C SFP module supports 10/100/1000 auto negotiation and auto MDI/MDIX. It can withstand rugged environments with operating temperatures of between -40 to +85°C. Our product is built to meet or exceed the specification of Avago ABCU-5741RZ-C= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.



Performance		Power	
SFP transceiver type *	Copper	Maximum voltage	4 V
Maximum data transfer rate *	1000 Mbit/s	Power consumption (typical)	1.3 W
Interface type *	SFP	Operational conditions	
Single-mode fiber (SMF) supported	✗	Minimum operating temperature	-40 °C
Multi-mode fiber (MMF) supported	✗	Maximum operating temperature	85 °C
SFP transceiver standard	TX	Operating temperature (T-T)	-40 - 85 °C
Maximum transfer distance	100 m	Storage temperature (T-T)	-40 - 85 °C
Ethernet LAN	✓	Operating relative humidity (H-H)	5 - 85%
Ethernet interface type	Gigabit Ethernet	Storage relative humidity (H-H)	5 - 85%
Networking standards	IEEE 802.3bq	Certificates	
Copper ethernet cabling technology	10BASE, 100BASE, 1000BASE	Waste Electrical and Electronic Equipment (WEEE) compliance	✓
Auto MDI/MDI-X	✓	Weight & dimensions	
Digital Diagnostics Monitoring (DDM)	✗	Width	13.4 mm
Features		Depth	56.5 mm
Product colour	Silver	Height	8.5 mm
Housing material	Metal	Weight	20 g
Plug and Play	✓	Packaging data	
Hot-Plug support	✓	Number of products included	1 pc(s)
Hot-swap	✓	Package type	Box
Easy to install	✓	Technical details	
Country of origin	China	Sustainability compliance	✓
Brand compatibility	Avago Technologies	Sustainability certificates	RoHS
Certification	CE, FCC, RoHS	Doesn't contain	Lead
Power		Compliance certificates	RoHS
Input voltage	3.3 V		



5056468750471

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.