## ATGBICS ABCU-5740ARZ Avago Broadcom Compatible Transceiver SFP 10/100/1000Base-T (RJ45, Copper, Ind Temp, 100m)

Brand : ATGBICS

Product code: ABCU-5740ARZ-C

Product name : ABCU-5740ARZ Avago Broadcom Compatible Transceiver SFP 10/100/1000Base-T (RJ45, Copper, Ind Temp, 100m)

ABCU-5740ARZ Avago Broadcom Compatible Transceiver SFP 10/100/1000Base-T (RJ45, Copper, Ind Temp, 100m)


ATGBICS ABCU-5740ARZ Avago Broadcom Compatible Transceiver SFP 10/100/1000Base-T (RJ45, Copper, Ind Temp, 100m):

ATGBICS ABCU-5740ARZ-C SFP operates on standard Category 5 unshielded twisted-pair copper cabling of link lengths up to 100m. Our Avago compatible ABCU-5740ARZ-C SFP module supports 10/100/1000 auto negotiation and auto MDI/MDIX. This product is suitable for industrial environments and can operate at temperatures between -40°C to 85°C. Our product is built to meet or exceed the specification of Avago ABCU-5740ARZ= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.





Performance		Power	
SFP transceiver type * Maximum data transfer rate * Interface type * Single-mode fiber (SMF) supported Multi-mode fiber (MMF) supported SFP transceiver standard Maximum transfer distance Ethernet LAN Ethernet interface type Networking standards Copper ethernet cabling technology Auto MDI/MDI-X	Copper 1000 Mbit/s SFP X TX 100 m Gigabit Ethernet IEEE 802.3bq 10BASE, 100BASE, 1000BASE	Input voltage Maximum voltage Power consumption (typical)	3.3 V 4 V 1.3 W
		Operational conditions Minimum operating temperature Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Certificates	-40 °C 85 °C -40 - 85 °C -40 - 85 °C 5 - 85% 5 - 85%
Digital Diagnostics Monitoring (DDM)	×	Waste Electrical and Electronic Equipment (WEEE) compliance	1
Features Product colour Housing material Plug and Play Hot-Plug support Hot-swap Easy to install Country of origin Brand compatibility Certification	Silver Metal	Weight & dimensions Width Depth Height Weight	13.4 mm 56.5 mm 8.5 mm 20 g
		Packaging data Number of products included Package type	1 pc(s) Box
		Technical details Sustainability compliance Doesn't contain Compliance certificates	✓ Lead RoHS



5056468750495

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.